

# Bodine BSL6LST LED Emergency Driver



Bodine BSL6LST Emergency LED Driver (6 Watts Output Power) New Compact Case Self-Testing Class 2 Output

## Benefits

New compact design for space-limited linear LED applications.

- Smart Charger Technology for low energy consumption
- Meets Title 20 CEC (California Energy Commission) efficiency standards
- Automatic code-compliant testing
- Controlled power for predictable discharge
- Poke-In wiring connections for simplified installation
- RoHS Compliant

## Specifications

UL Listed for US and Canada

Listed to UL924 and tested to CSA 22.2 No. 141

Field or Factory Installation (Indoor and Damp)

Output Class 2 Compliant

Illumination Time

90 Minutes

Initial Light Output

Up to 780 lumens\*

Full Warranty

5 Years (NOT pro-rata)

## Universal Input Voltage

120-277 VAC, 50/60 Hz

## Output Voltage

15 – 54 VDC

## Output Power

6.0 W initial (regulated)

## Test Switch / Charging Indicator Light

Two-Wire Illuminated Test Switch (2W-ITS)\*\*

## Battery

High-Temperature, Maintenance-Free

Lithium Ion Battery

7- to 10-Year Life Expectancy

## Recharge Time

24 Hours

## Temperature Rating

Ambient : 0°C to +55°C (32°F to 131°F)

Case: Tc (max): 63°C

## Dimensions

14.1" x 1.18" x 1.0" (358 mm x 30 mm x 25 mm) Mounting Center  
13.78" (350 mm)

## Weight

0.75 lbs. (0.34 kg)

For other items like the Bodine BSL6LST LED Emergency Driver  
click [here](#).

For more information on Bodine's line of lighting solutions  
click [here](#).