

Bodine B100 Emergency Ballast



Convenient Code-Compliance Dry or Damp Locations End-of-Lamp-Life Compatible Product order number: B100 (metal case)

Benefits: • Dry or Damp Locations • Emergency mode lumen output up to 450 lumens • End-of-Lamp-Life Compatible

Dimensions 9.4" x 2.4" x 1.5" (mounting center – 8.9")

Specifications:

UL Listed (UL924 Emergency Lighting Equipment)

Factory or Field Installation

(Dry or Damp)

Illumination Time

90 Minutes (Standard)

Initial Light Output

350 – 450 Lumens

Full Warranty

1 Year (NOT pro-rata)

Dual Input Voltage

120/277 VAC, 60 Hz

AC Input Current

280 mA

AC Input Power Rating

2.5 Watts

Test Switch

Single Pole

Battery

High-Temperature, Maintenance-Free

Nickel-Cadmium Battery

7- to 10-Year Life Expectancy

Battery Charging Current

280 mA

Recharge Time

24 Hours

Charging Indicator Light

LED

Ballast Temperature Rating (Ambient)

0°C to +50°C (32°F to 122°F)

(Damp Location)

0°C to +55°C (32°F to 131°F)

(Dry Location)

Dimensions

9.4" x 2.4" x 1.5" (238 mm x 60 mm x 38 mm)

Mounting Center 8.9" (226 mm)

Weight

2.1 lbs. (1.13 kg)