

# Bodine Ballast

# B50ST

# Emergency



Bodine B50ST Emergency Ballast. provides automatic code compliant testing and is compatible with linear fluorescent lamps. Up to 1400 lumens. Universal and self testing. Automatic code-compliant testing; For damp locations; One- or two- lamp emergency illumination; Universal input voltage; End-of-lamp-life compatible.

UL Listed For US and Canada  
Factory or Field Installation  
(Indoor and Damp)

Illumination Time  
90 Minutes

Initial Light Output  
900 – 3500 Lumens

Full Warranty  
5 Years (NOT pro-rata)

Universal Input Voltage  
120-277 VAC, 50/60 Hz

AC Input Current  
110 mA

AC Input Power Rating  
8.5 Watts

Test Switch/Charging Indicator Light  
Two-Wire Illuminated Test Switch (2W-ITS)

Battery  
High-Temperature, Maintenance-Free  
Nickel-Cadmium Battery  
7- to 10-Year Life Expectancy

Battery Charging Current  
280 mA

Recharge Time  
24 Hours

Charging Indicator Light  
LED

Temperature Rating (Ambient)  
0°C to +50°C (32°F to 122°F)

Dimensions  
16.6" x 2.8" x 2.85"  
(422 mm x 71 mm x 73 mm)  
2' (610 mm) Flexible Conduit  
Mounting Center 16.05" (408mm)

Weight  
7.5 lbs. (3.41 kg)

Model B30ST is warranted for five (5) full years from date of purchase. Please see detailed warranty information on the Signify official website.

For other items like the Bodine B50ST Emergency Ballast click [here](#).

For more information on Bodine's line of lighting solutions click [here](#).