

Bodine BSL310LPST LED Emergency Driver



Bodine BSL310LPST LED Emergency Driver. Low-Profile Emergency LED Driver, Self-Testing, Class 2 Output, 10 Watts Output Power.

Benefits:

- UL Listed for factory or field installation
- Compact design for low-profile/space-limited fixtures
- Controlled power for predictable discharge
- Smart Charger Technology for low energy consumption
- Meets CEC Title 20 (California Energy Commission) efficiency standards
- Class 2 output – UL 1310 Certified, CSA 22.2 No 223-M91 compliant
- Emergency mode initial lumen output of up to 1300 lumens
- Compatible with AC drivers and LED loads rated for Class 2
- Automatic adjustment for LED load configurations within the voltage range of 15 – 52V
- RoHS Compliant

Specifications

UL Listed for US and Canada

Listed to UL924 and tested to CSA 22.2, No. 141

For Field or Factory Installation

(Indoor and Damp)

Illumination Time

90 Minutes

Full Warranty

5 Years (NOT pro-rata)

Universal Input Voltage

120-277 VAC, 50/60 Hz

AC Input Power Rating

4 W (Maximum)

Output Voltage

15 – 52 VDC

Output Power

10.0 W initial (regulated)

NFPA-101 and NEC 700.12 compliant

Test Switch / Charging Indicator Light

Two-Wire Illuminated Test Switch (2W-ITS)

Battery

High-Temperature, Maintenance-Free

Nickel-Cadmium Battery

7- to 10-Year Life Expectancy

Recharge Time

24 Hours

Temperature Rating (Ambient)

0°C to +55°C (32°F to 131°F)

Case: Tc (max): 65°C

Dimensions

22.5" x 1.18" x 1.18" (572 mm x 30 mm x 30 mm)

Mounting Center 22.1" (561 mm)

Weight

2.5 lbs. (1.12 kg) – metal case without conduit

For other items like the Bodine BSL310LPST LED Emergency Driver [click here](#).

For more information on Bodine's line of lighting solutions [click here](#).