

Bodine BSL20-HV LED Emergency Driver



Bodine BSL20-HV LED Emergency Driver. Emergency LED Driver, Listed for Field Installation, High Output, 20 Watts Constant Output Power. 0.16A-0.10A 125V-200V

Benefits:

Smart Charger Technology for low energy consumption

Meets CEC Title 20 (California Energy Commission) efficiency standards

Listed for field or factory installation – UL 924 and CSA C22.2 No. 141 Emergency Lighting Compliant

Class 2 output – UL 1310 Certified, CSA 22.2 No 223-M91 compliant (BSL20LV only)

Emergency mode nominal lumen output of up to 2,600 lumens

Universal input (120-277 VAC)

2 wire input to help reduce wiring errors

Auto-sensing output within each range

RoHS Compliant

Specifications

UL Listed for US and Canada Listed to UL924 and tested to CSA 22.2 No. 141 For Field or Factory Installation (Indoor and Damp)

Illumination Time 90 Minutes

Full Warranty 5 Years (NOT pro-rata)

Universal Input Voltage 120-277 VAC, 50/60 Hz

AC Input Power Rating 8.5 W Maximum

Output Current and Voltage BSL20LV 1A-0.40A 20V-50V (Class 2)
BSL20MV 0.40A-0.15A 50V-130V BSL20HV 0.16A-0.10A 125V-200V

Output Power 20.0 W

Test Switch/Charging Indicator Light Illuminated Test Switch
2W-ITS (2W-ITS can be mounted up to 50 feet from fixture)

Battery High-Temperature, Maintenance-Free Nickel-Cadmium
Battery 7- to 10-Year Life Expectancy

Recharge Time 24 Hours

Temperature Rating (Ambient) 0°C to +50°C (32°F to 122°F)

Dimensions 16.6" x 2.8" x 2.85" (422 mm x 71 mm x 73 mm) 2'
(610 mm) Flexible Conduit Mounting Center 16.05" (408mm)

Weight 7.1 lbs. (3.22 kg)

For other items like the Bodine BSL20-HV LED Emergency Driver
click [here](#).

For more information on Bodine's line of lighting solutions
click [here](#).