

Dual USB Charger with 15/20A Duplex Tamper Resistant Receptacle

Model No.: 61501-TR2USB
62001-TR2USB



Description:

The 61501/62001-TR2USB USB Charger/Tamper-Resistant Receptacle offers two “Smart” USB charging ports and duplex Tamper-Resistant Receptacles. This device is able to deliver the optimum current accordingly to the device types and models attached, and charge any two devices up to 4.0 Amp charging capacity simultaneously, including smart phones, tablets, e-readers, cameras and MP3 players. The receptacle is back and side wired for broad compatibility with diverse wiring needs. The product can fit in any standard in-wall outlet box. All you will need is a USB cable to connect to one of the two USB ports.

Features:

- Dual “Smart” USB ports with a super high-current power of Max 2.4Amp or 4 Amp total, 5VDC
- Charge the most compatible electric devices directly without an adapter
- Tamper-Resistant Shutters provide compliance with 2011 NEC Article 406.12 for tamper-resistant receptacles
- Replace a standard duplex receptacle
- Back and side wire for easy installation
- UL/CUL Listed

Specifications:

Receptacle Rating	15/20 A, 125VAC
USB Rating.....	Two USB ports with total 4 Amp, 5VDC
Wire Terminals	#14-#12 AWG
Operating Temperature	-4 to 140°F (-20 to 60°C)
USB Compatibility	support USB 2.0, including Apple products
Warranty.....	2 Years

Application:

- | | | |
|--|--|---|
| <ul style="list-style-type: none"> • Cafes • Office • Kitchens • | <ul style="list-style-type: none"> • Bedrooms • Restaurants • Meeting rooms | <ul style="list-style-type: none"> • Airport Lounges • Labs • Hotels |
|--|--|---|

Compatibility:

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> ✓ iPad® and iPad® Mini ✓ iPhone® ✓ iPod® | <ul style="list-style-type: none"> ✓ Tablets ✓ Android Phones ✓ GPS ✓ Bluetooth® Headsets | <ul style="list-style-type: none"> ✓ Other USB Compatible product ✓ Digital Cameras |
|--|---|---|

Dual USB Charger with 15/20A Duplex Tamper Resistant Receptacle

Model No.: 61501-TR2USB2
62001-TR2USB2



Description:

The 61501/62001-TR2USB2 USB Charger/Tamper-Resistant Receptacle offers two USB charging ports and duplex Tamper-Resistant Receptacles. This device is able to deliver the optimum current accordingly to the device types and models attached, and charge any two devices up to 2.1 Amp charging capacity simultaneously, including smart phones, tablets, e-readers, cameras and MP3 players. The receptacle is back and side wired for broad compatibility with diverse wiring needs. The product can fit in any standard in-wall outlet box. All you will need is a USB cable to connect to one of the two USB ports.

Features:

- Dual USB ports with a super high-current power of Max 2.1 Amp total, 5VDC
- Charge the most compatible electric devices directly without an adapter
- Tamper-Resistant Shutters provide compliance with 2011 NEC Article 406.12 for tamper-resistant receptacles
- Replace a standard duplex receptacle
- Back and side wire for easy installation
- UL/CUL Listed

Specifications:

Receptacle Rating	15/20 A, 125VAC
USB Rating.....	Two USB ports with total 2.1 Amp, 5VDC
Wire Terminals	#14-#12 AWG
Operating Temperature	-4 to 140°F (-20 to 60°C)
USB Compatibility	support USB 2.0, including Apple products
Warranty.....	2 Years

Application:

- | | | |
|--|--|---|
| <ul style="list-style-type: none"> • Cafes • Office • Kitchens • | <ul style="list-style-type: none"> • Bedrooms • Restaurants • Meeting rooms | <ul style="list-style-type: none"> • Airport Lounges • Labs • Hotels |
|--|--|---|

Compatibility:

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> ✓ iPad® and iPad® Mini ✓ iPhone® ✓ iPod® | <ul style="list-style-type: none"> ✓ Tablets ✓ Android Phones ✓ GPS ✓ Bluetooth® Headsets | <ul style="list-style-type: none"> ✓ Other USB Compatible product ✓ Digital Cameras |
|--|---|---|

4-Port USB Charger
Model No.: 62000-4USB



Description:

The 62000-4USB USB Charger offers four USB charging ports. This 62000-4USB is able to charge any current electronic devices simultaneously including smart phones, tablets, e-readers, cameras rating in the future. All you will need is a USB cable to connect to one of the four USB ports.

Features:

- 4 USB ports with a super high-current power of 4 Amp total, 5VDC
- Charge most compatible electrical device directly without an adapter
- Two Free wall Plates, screwless and standard wall plate, provide the best combination of appearance and functionality
- Replace a standard duplex receptacle
- Back and side wire for easy installation
- If the devices combined power requirements exceed the power capacity of the USB ports, the charger will automatically shut down to protect your devices.

Specifications:

USB Rating.....Two USB ports with total 4 Amp, 5VDC
Wire Terminals#14-#12 AWG
Operating Temperature..... -4 to 140°F (-20 to 60°C)
USB Compatibility USB 1.1/2.0/3.0 devices, including Apple products
Warranty..... 2 Years

Application:

- Cafes
- Office
- Kitchens
- Bedrooms
- Restaurants
- Meeting rooms
- Airport Lounges
- Labs
- Hotels

Compatibility:

- ✓ iPad® and iPad® Mini
- ✓ iPhone®
- ✓ iPod®
- ✓ Tablets
- ✓ Android Phones
- ✓ GPS
- ✓ Bluetooth® Headsets
- ✓ Digital Cameras
- ✓ Other USB Compatible product

**Ultra High Speed USB Interchangeable Module
Charger 15/20A Receptacle**

61150-TR2USB-CU
61200-TR2USB-CU



Description:

Enerlites TR2USB-CU, is the Industry's first 4.8A, 5VDC interchangeable dual USB charger with 15A or 20A tamper resistant receptacle. Our High Speed USB ports deliver the most advance charging needs of each device simultaneously and optimizes the current by a smart chip to reduce charging time. Our high speed USB chargers give you the ability to charge virtually any device without the use of bulky adapters that can be lost or misplaced, while continuing to power traditional electronics, i.e. lamp or television in the same receptacle.

Features:

- Industry's first Dual Ultra High Speed USB charger at 4.8Amp, 5VDC.
- Charge most compatible electronic devices directly without an adapter
- Tamper-Resistant Shutters, compliance with 2011 NEC
- Replace a standard duplex receptacle
- Back and side terminals for easy installation
- UL/CUL Listed
- Available color module in white, black , light almond and ivory

Specifications:

Receptacle Rating	15A or 20A, 125VAC
Ultra High Speed USB	Maximum at 4.8Amp, 5VDC
Terminals	#14-#12 AWG
Operating Temperature	-4 to 140°F (-20 to 60°C)
Receptacle Dimension	2-3/4"x2"x2-3/4"
Interchangeable USB Color Module.....	...Sold Separately

Application:

- | | | |
|---|--|---|
| <ul style="list-style-type: none"> • Cafeterias • Offices • Kitchens | <ul style="list-style-type: none"> • Bedrooms • Restaurants • Meeting rooms | <ul style="list-style-type: none"> • Airport Lounges • Labs • Hotels |
|---|--|---|

Compatibility:

- | | | |
|--|---|---|
| <ul style="list-style-type: none"> ✓ iPad® and iPad® Mini ✓ iPhone® ✓ iPod® | <ul style="list-style-type: none"> ✓ Tablets ✓ Android Phones ✓ GPS ✓ Bluetooth® Headsets | <ul style="list-style-type: none"> ✓ Digital Cameras ✓ Other USB Compatible product |
|--|---|---|

Enerlites Inc.

www.enerlites.com

Phone: 949-756-0536 Fax: 949-756-0528 e-mail: sales@enerlites.com

Version 2.0

Date: 12/20/2015

**Ultra High Speed Dual USB Charger with 15/20A
Duplex Tamper Resistant Receptacle
Interchangeable Face Cover**

61501-TR2USB-CC
62001-TR2USB-CC



Description:

Enerlites TR2USB-CC, is the Industry's first 4.8A, 5VDC interchangeable face dual USB charger with 15A or 20A tamper resistant receptacle. Our High Speed USB ports deliver the most advance charging needs of each device simultaneously and optimizes the current by a smart chip to reduce charging time. Our high speed USB chargers give you the ability to charge virtually any device without the use of bulky adapters that can be lost or misplaced, while continuing to power traditional electronics, i.e. lamp or television in the same receptacle.

Features:

- Industry's first dual USB high speed charger at 4.8amp, 5VDC
- Charge most compatible electronic devices directly without an adapter
- Tamper-Resistant Shutters, compliance with 2011 NEC code
- Replace a standard duplex receptacle
- Back and side terminals for easy installation
- UL/CUL Listed

Specifications:

Receptacle Rating	15A or 20A, 125VAC
High Speed USB	Maximum at 4.8Amp, 5VDC
Back and Side Terminals.....	#14-#12 AWG
Operating Temperature	-4 to 140°F (-20 to 60°C)
Receptacle Dimension	2-3/4"x2"x2-3/4"
Interchangeable face cover (Almond, White and Black).....	included

Application:

- Cafeterias
- Offices
- Kitchens
- Bedrooms
- Restaurants
- Meeting rooms
- Airport Lounges
- Labs
- Hotels

Compatibility:

- ✓ iPad® and iPad® Mini
- ✓ iPhone®
- ✓ iPod®
- ✓ Tablets
- ✓ Android Phones
- ✓ GPS
- ✓ Bluetooth® Headsets
- ✓ Digital Cameras
- ✓ Other USB Compatible product